

DIRECTORATE GENERAL NATIONAL DISASTER RESPONSE FORCE
NDCC-II BUILDING, 6th FLOOR, JAI SINGH ROAD,
NEW DELHI-110 001

CORRIGENDUM NOTICE NO-01
(Consisting of 02 pages only)

No. 1-17018/PROC (I)/1236/HQ-NDRF/2026- 2117

Dated, the 19th August 2026

Reference to this NDRF HQ GeM Bid No. GEM/2026/B/7657141 dated 15/07/2026.

2. In partial modification to this HQ GeM Bid No. GEM/2026/B/7657141 dated 15/07/2026 in c/w procurement of 17 Nos Drones for NDRF Bns. The Revise Technical Specification & Trial directives of above are as under: -

S/No.	Parameter	For	Read As
1.3	One Payload assembly consist of	a) Day Camera only b) Night Camera only c) Day & Night Camera payload(both) d) Integrated day and night camera (as per user requirement) Optional for Training UAV	One Payload assembly consist of Integrated day and night camera
2.1	Role	Surveillance, reconnaissance and detection during day and night.	Surveillance during day and night.
2.5	Flight Modes	f) Vision based Autonomous Target Tracking of fixed and moving targets	f) Omitted
2.6	Endurance	a) 40 minutes or more with all payloads at MSL. Reduction in endurance of 10% for every increase of 1000M AMSL.	a) 30 minutes or more with all payloads at MSL. Reduction in endurance of 10% for every increase of 1000M AMSL.
2.9	Range of Operation (in Km)	a) Minimum 5 km line of sight	Minimum 2 km line of sight
2.10	Cruise Speed (In Km/h)	40 km/h or more	20 km/h or more
2.11	Operating Wind Conditions (In Km/h)	a) Take off: 30 km/h or more b) Landing: 30 Km/h or more c) Operate:30 Km/h or more	a) Take off: 20 km/h or more b) Landing: 20 Km/h or more c) Operate:20 Km/h or more
2.12	Failsafe features	c) i) Multiple GNSS on-board for GPS failure redundancy ii) (Including NAVIC)	Standard GNSS/GPS/NAVIC
3.1	Payloads required	One Payload assembly consist of a) Day & Night Camera payload (both)	One Payload assembly consist of: Integrated day and night camera
3.2	Payload and Video Stabilization	a) All payloads should be gimbals stabilized on- board. b) Video output should be digitally/gimbal stabilized at all zoom levels. c) Quality of video should not be affected by UAV vibrations.	a) All payloads should be gimbals stabilized (with or without EIS) on-board. b) Video output should be digitally/gimbal stabilized at all zoom levels.

→ 52 →

			c) Quality of video should not be affected by UAV vibrations
3.4	Thermal Imager (TI) Night Payload	a) Thermal Camera with 360° pan and 90° tilt control during flight. b) Resolution: 640 X 480 pixels or better c) White/Black Hot modes d) Digital Zoom: 4X or more	Omitted
3.5	Target Detection Recognition, Identification	Day Payload	Omitted
		Vehicle Size (4.5 x 1.5M)	Omitted
4.1	a) Semi ruggedized Min – 7 inch tablet	Firm will submit certificate of Govt Lab or NABL accredited or ILAC accredited laboratory	a) Semi ruggedized Min – 7 inch tablet
4.3	Battery Operation	Minimum 2 hours at peak utilization	Capable of sustaining a minimum continuous flight time of 30 minutes at defined speed and payload
4.10	Payload Controls	a) Toggle for selection and switch payload b) Pan/Tilt/Zoom Controls c) Point payload to ground co-ordinate function d) Recording on/off	a) Pan/Tilt/Zoom Controls b) Point payload to ground co-ordinate function c) Recording on/off
4.11	Button based/USB Joystick Controls	1. Full Camera Control Pan/Tilt Zoom In/Out Black/White Hot ii RPV Mode iii Altitude Control	1. Full Camera Control Pan/Tilt Zoom In/Out 2. RPV Mode 3. Altitude Control
5.2	Data Link	S/C band (2 GHz to 6 GHz) with Minimum 128 bit AEC Encryption	S/C band (2 GHz to 6 GHz)
6.7	Battery of AV	The intelligent standard lithium-based battery pack should have the backup of minimum 40 minutes	The intelligent standard lithium-based battery pack should have the backup of minimum 30 minutes
7.6	Training Simulator with RC option		Omitted

Note: - Remaining terms and conditions of the GeM bid will remain unchanged.


 (Deepak Talwar)
 Second-In-Command (Prov/Proc)
 HQ NDRF

Copy to :-

1. R&D Cell for information and N/A Pse.
2. IT Cell HQ NDRF for info with request to publish on NDRF website upto 30/10/2026