


65. DISTRESS SIGNAL UNIT

General		Picture of Equipment
		
1.	Size	Small and compact that could be attached to the waist belt with on/off key.
2.	Audio output	Not less than 90 Db at 3 meter distance
3.	Led indicator	Green LED show unit is on and Red LED to show when unit has raised distress alarm.
4.	Battery	Compatible with Distress Signal Unit
5.	Stand by Battery nlife	Minimum 100 hrs stands by life after full charge.
6.	Distree Alarm	Not less than 2 audio signals per second at full noise level.
7.	Weight	Not more 350 Gm
<p>APPROVAL The distress Signal Unit shall carry national/international certification for use by the emergency service personnel and the relevant documnt shall be submitted along with the offer.</p>		
<p>WARRANTY : The Distress Signal Unit offered shall carry warranty for not less than 02 years.</p>		
<p>TECHNICAL EVALUATION: The technical evaluation of DSU shall be subject to the following.</p> <ul style="list-style-type: none"> a) Meeting the requirement as mentioned from SL No. 1 TO 4 above. b) Design in conformity to EN/DIN/US standards and certificate to be submitted alongwith the offer and. Weight of DSU subject to compliance in all other respect the units shall be listed in descending order lightest on top and the financial bid shall be opened in respect of first five bidders and the lowest financial offer would be selected. 		